



# Chicago Pneumatic

# Vehicle Service Tools



*HR S / Hose Reel  
Small Closed  
Composite Series*



*HR M / Hose Reel  
Medium Closed  
Steel Series*



*HRO L / Hose Reel  
Large Open  
Steel Series*



*HRO M / Hose Reel  
Medium Open  
Steel Series*

- ▶ *No hose on the ground*
- ▶ *Supplied with a swivel-plate*
- ▶ *High airflow for maximum productivity*
- ▶ *Lightweight and resistant polyurethane hose*
- ▶ *Also available with rubber hose: HRO M and HRO L (BSP and NPT)*



*Use with Chicago Pneumatic :  
Impact wrenches, drills, ratchets,  
grinders, palm sanders*

## AIR HOSE REELS

## Maximize your tool

# Combine safety and productivity with this quality hose reel line



## CUSTOMER BENEFITS

- No hose on the ground for an improved safety environment
- From 1 to 10 / 15 or 16 meters hose lengths with feedback force for a clean work space
- Directional swivel-plate to help you reach correctly your application
- High airflow for maximum productivity
- Lightweight and flexible polyurethane hose for less work fatigue
- Open Reels with Rubber hose available for heavy-duty grinding/spark areas

## APPLICATIONS

- Workshops and service stations in the automotive, truck, earthmoving and farming
- Petrol stations



### **A** HR S / Hose Reel Small Closed Composite Series

Compact and ergonomic plastic casing air hose reel  
Airflow > 7 l/s

### **B** HR M / Hose Reel Medium Closed Steel Series

Heavy-duty air hose reels in steel for longest lifetime  
Airflow > 10 l/s

### **C** HRO M / Hose Reel Medium Open Steel Series

Heavy-duty air hose reel in industrial quality  
Airflow > 8.5 l/s

### **D** HRO L / Hose Reel Large Open Steel Series

Heavy-duty air hose reel in industrial quality  
Airflow > 16 l/s

PIC REF	MODEL	PART NUMBER	THREAD TYPE	CONNECTION		LENGTH		Ø INTERNAL		FLUID	HOSE MATERIAL	INLET	WEIGHT		MAX PRESSURE		AIR FLOW	
				IN (in.)	OUT (in.)	m	feet	mm	in.				kg	lbs.	Bar	PSI	l/s	Cfm
A	HR S HOSE REEL	615 804 5020	BSP	1/4	1/4	10	33	8	5/16	Air	100% Polyurethane	1 m/3.3 feet lead-hose	4.5	9.9	16	232	7	14.12
A	HRN S HOSE REEL	615 804 5030	NPT	1/4	1/4	10	33	8	5/16	Air	100% Polyurethane	1 m/3.3 feet lead-hose	4.5	9.9	16	232	7	14.12
B	HR M HOSE REEL	615 804 5040	BSP	1/4	1/4	12	39	10	3/8	Air	100% Polyurethane	1.5 m/4.92 feet lead-hose	8.5	18.7	20	290	10	21.19
B	HRN M HOSE REEL	615 804 5050	NPT	1/4	1/4	12	39	10	3/8	Air	100% Polyurethane	1.5 m/4.92 feet lead-hose	8.5	18.7	20	290	10	21.19
C	HRO M HOSE REEL	615 804 5060	BSP	1/4	1/4	16	52	10	3/8	Air	100% Polyurethane	1.5 m/4.92 feet lead-hose	11	24.3	20	290	8.5	17.65
C	HROR M HOSE REEL	615 804 5100	BSP	3/8	3/8	15	49	10	3/8	Air/Water	Rubber (SBR+NR /SBR+EPDM)	1.5 m/4.92 feet lead-hose	11	24.3	20	290	8.5	17.65
C	HRNO M HOSE REEL	615 804 5070	NPT	1/4	1/4	16	52	10	3/8	Air	100% Polyurethane	1.5 m/4.92 feet lead-hose	11	24.3	20	290	8.5	17.65
C	HRNOR M HOSE REEL	615 804 5110	NPT	3/8	3/8	15	49	10	3/8	Air/Water	Rubber (SBR+NR /SBR+EPDM)	1.5 m/4.92 feet lead-hose	11	24.3	20	290	8.5	17.65
D	HRO L HOSE REEL	615 804 5080	BSP	3/8	3/8	16	52	13	1/2	Air	100% Polyurethane	1.5 m/4.92 feet lead-hose	14	30.9	20	290	16	33.55
D	HROR L HOSE REEL	615 804 5120	BSP	3/8	3/8	15	49	13	1/2	Air/Water	Rubber (SBR+NR /SBR+EPDM)	1.5 m/4.92 feet lead-hose	14	30.9	20	290	16	33.55
D	HRNO L HOSE REEL	615 804 5090	NPT	3/8	3/8	16	52	13	1/2	Air	100% Polyurethane	1.5 m/4.92 feet lead-hose	14	30.9	20	290	16	33.55
D	HRNOR L HOSE REEL	615 804 5130	NPT	3/8	3/8	15	49	13	1/2	Air/Water	Rubber (SBR+NR /SBR+EPDM)	1.5 m/4.92 feet lead-hose	14	30.9	20	290	16	33.55



Visit our website or your Authorized CP Distributor for parts and accessories.  
[www.cp.com](http://www.cp.com)

Form #  
8940165027  
01/08